

CONDITIONS OF APPROVAL

(As Modified by the City Planning Commission at its meeting on April 24, 2025)

BUREAU OF ENGINEERING - SPECIFIC CONDITIONS

Any questions regarding these conditions should be directed to Quyen Phan of the Permit Case Management Division, located at 201 North Figueroa Street, Suite 290, or by e-mailing quyen.phan@lacity.org.

1. That a 5-foot wide strip of land be dedicated along Preuss Road adjoining the tract to complete a 30-foot wide half right-of-way in accordance with Local Street standards.
2. That a 2.5-foot wide strip of land be dedicated along the alley adjoining the tract to complete 10-foot wide half alley.
3. That the 5-foot wide water easement within the tract boundary be shown on the final map.
4. That if this tract map is approved as "Small Lot Subdivision" then, and if necessary for street address purposes, all the common access to this subdivision be named on the final map satisfactory to the City Engineer.
5. That if this tract map is approved as small lot subdivisions, then the final map be labeled as "Small Lot Subdivision per Ordinance No. 185462" satisfactory to the City Engineer.
6. That all common access easements including the vehicular access and pedestrian access easement be part of the adjoining lots.
7. That if necessary, public sanitary sewer easements be dedicated on the final map based on an alignment by the Central Engineering District Office.
8. That if necessary, the owners of the property record an agreement satisfactory to the City Engineer that they will provide name signs for the common access driveways.
9. That the subdivider make a request to the Central District Office of the Bureau of Engineering to determine the capacity of existing sewers in this area.
10. That all pedestrian common access easements be shown on the final map.

DEPARTMENT OF BUILDING AND SAFETY, GRADING DIVISION

Grading Division approvals are conducted at 221 North Figueroa Street, 12th Floor. The approval of this Tract Map shall not be construed as having been based upon geological investigation such as will authorize the issuance of building permits on the subject property. Such permits will be issued only at such time as the Department of Building and Safety has received such topographic maps and geological reports as it deems necessary to justify the issuance of such building permits.

11. No structures for human occupancy shall be located to the east of the 5-foot fault setback zone depicted on the Site Map of the 03/24/2023 report. If structures for human occupancy are proposed in this area, submit a supplemental report to the Grading Division for review and approval.

12. The project engineering geologist shall observe all final removal excavations to verify that the conclusions of the current fault investigation are correct and that no fault trace or evidence of ground deformation are exposed in the excavation. Each panel of the shoring excavation shall be logged prior to installation of lagging and a field memo documenting that the panel has been logged shall be prepared for review by the Deputy Grading Inspector and Building inspector(s). A supplemental report that summarizes the geologist's observations shall be submitted to the Grading Division of the Department upon completion of the excavations. If evidence of faulting is observed, the Grading Division shall be notified and a site meeting scheduled.
13. The entire site shall be brought up to the current Code standard (7005.9).
14. Approval shall be obtained from the Department of Public Works, Bureau of Engineering, Development Services and Permits Program for the proposed removal of support and/or retaining of slopes adjoining to public way (3307.3.2).

201 N. Figueroa Street 3rd Floor, LA

(213) 482-7045

15. Secure the notarized written consent from all owners upon whose property proposed grading/construction access is to extend, in the event off-site grading and/or access for construction purposes is required (7006.6). The consent shall be included as part of the final plans.
16. The geologist and soils engineer shall review and approve the detailed plans prior to issuance of any permits. This approval shall be by signature on the plans that clearly indicates the geologist and soils engineer have reviewed the plans prepared by the design engineer; and, that the plans include the recommendations contained in their reports (7006.1).
17. All recommendations of the reports that are in addition to or more restrictive than the conditions contained herein shall be incorporated into the plans.
18. A copy of the subject and appropriate referenced reports and this approval letter shall be attached to the District Office and field set of plans (7006.1). Submit one copy of the above reports to the Building Department Plan Checker prior to issuance of the permit.
19. A grading permit shall be obtained for all structural fill and retaining wall backfill (106.1.2).
20. All man-made fill shall be compacted to a minimum 90 percent of the maximum dry density of the fill material per the latest version of ASTM D 1557. Where cohesionless soil having less than 15 percent finer than 0.005 millimeters is used for fill, it shall be compacted to a minimum of 95 percent relative compaction based on maximum dry density. Placement of gravel in lieu of compacted fill is only allowed if complying with LAMC Section 91.7011.3.
21. Existing uncertified fill shall not be used for support of footings, concrete slabs or new fill (1809.2, 7011.3).
22. Drainage in conformance with the provisions of the Code shall be maintained during and subsequent to construction (7013.12).
23. Grading shall be scheduled for completion prior to the start of the rainy season, or detailed temporary erosion control plans shall be filed in a manner satisfactory to the Grading Division of the Department and the Department of Public Works, Bureau of Engineering, 8-Permit Section, for any grading work in excess of 200 cubic yards (7007.1).

201 N. Figueroa Street 3rd Floor, LA

(213) 482-7045

24. All loose foundation excavation material shall be removed prior to commencement of framing. Slopes disturbed by construction activities shall be restored (7005.3).
25. The applicant is advised that the approval of this report does not waive the requirements for excavations contained in the General Safety Orders of the California Department of Industrial Relations (3301.1).
26. Temporary excavations that remove lateral support to the public way, adjacent property, or adjacent structures shall be supported by shoring, as recommended. Note: Lateral support shall be considered to be removed when the excavation extends below a plane projected downward at an angle of 45 degrees from the bottom of a footing of an existing structure, from the edge of the public way or an adjacent property. (3307.3.1)
27. Prior to the issuance of any permit that authorizes an excavation where the excavation is to be of a greater depth than are the walls or foundation of any adjoining building or structure and located closer to the property line than the depth of the excavation, the owner of the subject site shall provide the Department with evidence that the adjacent property owner has been given a 30-day written notice of such intent to make an excavation (3307.1).
28. The soils engineer shall review and approve the shoring plans prior to issuance of the permit (3307.3.2).
29. Prior to the issuance of the permits, the soils engineer and/or the structural designer shall evaluate the surcharge loads used in the report calculations for the design of the retaining walls and shoring. If the surcharge loads used in the calculations do not conform to the actual surcharge loads, the soil engineer shall submit a supplementary report with revised recommendations to the Department for approval.
30. Shoring shall be designed for a minimum EFP of 67 PCF; all surcharge loads shall be included into the design, as recommended.
31. Shoring shall be designed for a maximum lateral deflection of 0.5 inch, as recommended.
32. A shoring monitoring program shall be implemented to the satisfaction of the soils engineer.
33. All foundations shall derive entire support from native undisturbed alluvial terrace soils, as recommended and approved by the geologist and soils engineer by inspection.
34. Foundations adjacent to a descending slope steeper than 3:1 (horizontal to vertical) in gradient shall be a minimum distance of one-third the vertical height of the slope but need not exceed 40 feet measured horizontally from the footing bottom to the face of the slope (1808.7.2).
35. Buildings adjacent to ascending slopes steeper than 3H:1V in gradient shall be setback from the toe of the slope a level distance measured perpendicular to slope contours equal to one-half the vertical height of the slope, but need not exceed 15 feet (1808.7.1).
36. Footings supported on approved compacted fill or expansive soil shall be reinforced with a minimum of four (4), ½-inch diameter (#4) deformed reinforcing bars. Two (2) bars shall be placed near the bottom and two (2) bars placed near the top of the footing.

37. The foundation/slab design shall satisfy all requirements of the Information Bulletin P/BC 2017- 116 "Foundation Design for Expansive Soils" (1803.5.3).
38. Slabs placed on approved compacted fill shall be at least 4 inches thick, as recommended, and shall be reinforced with ½-inch diameter (#4) reinforcing bars spaced a maximum of 16 inches on center each way.
39. Concrete floor slabs placed on expansive soil shall be placed on a 4-inch fill of coarse aggregate or on a moisture barrier membrane. The slabs shall be at least 4 inches thick, as recommended, and shall be reinforced with ½-inch diameter (#4) reinforcing bars spaced a maximum of 16 inches on center each way.
40. The seismic design shall be based on a Site Class D, as recommended. All other seismic design parameters shall be reviewed by LADBS building plan check.
41. Retaining walls shall be designed for the lateral earth pressures specified in the section titled "Retaining Walls" starting on page 9 of the 03/24/2023 report. All surcharge loads shall be included into the design.
42. Retaining walls higher than 6 feet shall be designed for lateral earth pressure due to earthquake motions as specified on the wall pressure analysis of the reference report (1803.5.12).
43. All retaining walls shall be provided with a standard surface backdrain system and all drainage shall be conducted in a non-erosive device to the street in an acceptable manner (7013.11).
44. With the exception of retaining walls designed for hydrostatic pressure, all retaining walls shall be provided with a subdrain system to prevent possible hydrostatic pressure behind the wall. Prior to issuance of any permit, the retaining wall subdrain system recommended in the soils report shall be incorporated into the foundation plan which shall be reviewed and approved by the soils engineer of record (1805.4).
45. Installation of the subdrain system shall be inspected and approved by the soils engineer of record and the City grading/building inspector (108.9).
46. Basement walls and floors shall be waterproofed/damp-proofed with an LA City approved "Below-grade" waterproofing/damp-proofing material with a research report number (104.2.6).
47. Prefabricated drainage composites (Miradrain, Geotextiles) may be only used in addition to traditionally accepted methods of draining retained earth.
48. The structures shall be connected to the public sewer system per P/BC 2020-027.
49. All roof, pad and deck drainage shall be conducted to the street in an acceptable manner in non-erosive devices or other approved location in a manner that is acceptable to the LADBS and the Department of Public Works; water shall not be dispersed on to descending slopes without specific approval from the Grading Division and the consulting geologist and soils engineer (7013.10).
50. All concentrated drainage shall be conducted in an approved device and disposed of in a manner approved by the LA DBS (7013.10).

51. Any recommendations prepared by the geologist and/or the soils engineer for correction of geological hazards found during grading shall be submitted to the Grading Division of the Department for approval prior to use in the field (7008.2, 7008.3).
52. The geologist and soils engineer shall inspect all excavations to determine that conditions anticipated in the report have been encountered and to provide recommendations for the correction of hazards found during grading (7008, 1705.6 & 1705.8).
53. Prior to pouring concrete, a representative of the consulting soils engineer shall inspect and approve the footing excavations. The representative shall post a notice on the job site for the LADBS Inspector and the Contractor stating that the work inspected meets the conditions of the report. No concrete shall be poured until the LADBS Inspector has also inspected and approved the footing excavations. A written certification to this effect shall be filed with the Grading Division of the Department upon completion of the work. (108.9 & 7008.2)
54. Prior to excavation an initial inspection shall be called with the LADBS Inspector. During the initial inspection, the sequence of construction; shoring; protection fences; and, dust and traffic control will be scheduled (108.9.1).
55. Installation of shoring shall be performed under the inspection and approval of the soils engineer and deputy grading inspector (1705.6, 1705.8).
56. Prior to the placing of compacted fill, a representative of the soils engineer shall inspect and approve the bottom excavations. The representative shall post a notice on the job site for the LADBS Inspector and the Contractor stating that the soil inspected meets the conditions of the report. No fill shall be placed until the LADBS Inspector has also inspected and approved the bottom excavations. A written certification to this effect shall be included in the final compaction report filed with the Grading Division of the Department. All fill shall be placed under the inspection and approval of the soils engineer. A compaction report together with the approved soil report and Department approval letter shall be submitted to the Grading Division of the Department upon completion of the compaction. In addition, an Engineer's Certificate of Compliance with the legal description as indicated in the grading permit and the permit number shall be included (7011.3).
57. No footing/slab shall be poured until the compaction report is submitted and approved by the Grading Division of the Department

DEPARTMENT OF BUILDING AND SAFETY, ZONING DIVISION

An appointment is required for the issuance of a clearance letter from the Department of Building and Safety. The applicant is asked to contact Laura Duong at (213) 482-0434 or laura.duong@lacity.org to schedule an appointment.

58. Obtain permits for the demolition or removal of all existing structures on the site. Accessory structures and uses are not permitted to remain on lots without a main structure or use. Provide copies of the demolition permits and signed inspection cards to show completion of the demolition work.
59. Lot 7 shall provide a 20 ft. setback as per the 20 ft. Building Line along Preuss Road. Revise the map to show compliance with the required setback per the 20 ft. Building Line or obtain approval from the Department of City Planning to remove the existing 20 ft. Building Line.

60. The submitted map does not comply with the maximum density (1,500 s.f. of lot area/dwelling unit) requirement of the RD1.5 Zone. A half of the alley can be used for density purposes. Revise the map to show compliance with the above requirement based on the lot area after required street dedication is taken or obtain approval from the Department of City Planning.
61. Show all street/alley dedications as required by Bureau of Engineering and provide net lot area after all dedication. "Area" requirements shall be re-checked as per net lot area after street dedication. Density and front and rear yard requirements shall be required to comply with current code as measured from new property lines after dedication.

Notes:

There is a 20 ft. Building Line along portion of Preuss Road for Proposed Lot 7.

Owners are to record a Maintenance Agreement that runs with the land for the purpose of reciprocal private easements maintenance program to all common areas and shared facilities such as trees, landscaping, drainage, trash, parking, community driveway (ground floor width and width clear to sky above the ground floor level), including walkways as shown on the approved Small Lot Subdivision Map.

The proposed building plans have not been checked for and shall comply with Building and Zoning Code requirements. With the exception of revised health or safety standards, the subdivider shall have a vested right to proceed with the proposed development in substantial compliance with the ordinances, policies, and standards in effect at the time the subdivision application was deemed complete. Plan check will be required before any construction, occupancy or change of use.

If the proposed development does not comply with the current Zoning Code, all zoning violations shall be indicated on the Map.

Backup space for parking space with less than 26'-8" shall provide sufficient parking stall width and garage door opening width to comply with the current Zoning Code requirement. Comply with the above requirement at the time of Plan Check or obtain City Planning approval.

DEPARTMENT OF RECREATION AND PARKS

Please contact RAP at (213) 202-2682 for any questions regarding the following:

62. That the Park Fee paid to the Department of Recreation and Parks be calculated as a Subdivision (Quimby in-lieu) fee.

DEPARTMENT OF TRANSPORTATION

Please contact the Department of Transportation at ladot.onestop@lacity.org for any questions regarding the following.

63. A minimum 20-foot reservoir space be provided between any security gate(s) and the property line, or as shall be determined to the satisfaction of the Department of Transportation.
64. Parking stalls shall be designed so that a vehicle is not required to back into or out of any public street or sidewalk (not applicable when driveways serve not more than two dwelling units and where the driveway access is to a street other than a major or secondary highway), LAMC 12.21 A.

65. A parking area and driveway plan be submitted to the Citywide Planning Coordination Section of the Department of Transportation prior to submittal of building permit plans for plan check by the Department of Building and Safety. Transportation approvals are conducted at 201 N. Figueroa Street Room 550. For an appointment, contact LADOT One Stop Counter portal at: ladot.onestop@lacity.org
66. That a fee in the amount of \$205 be paid for the Department of Transportation as required per Ordinance No. 180542 and LAMC Section 19.15 prior to recordation of the final map. Note: the applicant may be required to comply with any other applicable fees per this new ordinance.

FIRE DEPARTMENT

*The applicant is further advised that all subsequent contact regarding these conditions must be with the Hydrant and Access Unit. This would include clarification, verification of condition compliance and plans or building permit applications, etc., and shall be accomplished **BY APPOINTMENT ONLY**, in order to assure that you receive service with a minimum amount of waiting please call (213) 482-6543. You should advise any consultant representing you of this requirement as well.*

67. Access for Fire Department apparatus and personnel to and into all structures shall be required.
68. Address identification. New and existing buildings shall have approved building identification placed in a position that is plainly legible and visible from the street or road fronting the property.
69. One or more Knox Boxes will be required to be installed for LAFD access to project. Location and number to be determined by LAFD Field Inspector. (Refer to FPB Req # 75).
70. The entrance or exit of all ground dwelling units shall not be more than 150 feet from the edge of a roadway of an improved street, access road, or designated fire lane.
71. No building or portion of a building shall be constructed more than 150 feet from the edge of a roadway of an improved street, access road, or designated fire lane.
72. Fire Lane Requirements:
- a) Fire lane width shall not be less than 20 feet. When a fire lane must accommodate the operation of Fire Department aerial ladder apparatus or where fire hydrants are installed, those portions shall not be less than 28 feet in width.
 - b) The width of private roadways for general access use and fire lanes shall not be less than 20 feet, and the fire lane must be clear to the sky.
 - c) Fire lanes, where required and dead ending streets shall terminate in a cul-de-sac or other approved turning area. No dead ending street or fire lane shall be greater than 700 feet in length or secondary access shall be required.
 - d) Submit plot plans indicating access road and turning area for Fire Department approval.
 - e) All parking restrictions for fire lanes shall be posted and/or painted prior to any Temporary Certificate of Occupancy being issued.

- f) Plans showing areas to be posted and/or painted, "FIRE LANE NO PARKING" shall be submitted and approved by the Fire Department prior to building permit application sign-off.
 - g) Electric Gates approved by the Fire Department shall be tested by the Fire Department prior to Building and Safety granting a Certificate of Occupancy.
 - h) All public street and fire lane cul-de-sacs shall have the curbs painted red and/or be posted "No Parking at Any Time" prior to the issuance of a Certificate of Occupancy or Temporary Certificate of Occupancy for any structures adjacent to the cul-de-sac.
 - i) No framing shall be allowed until the roadway is installed to the satisfaction of the Fire Department.
73. Construction of public or private roadway in the proposed development shall not exceed 10 percent in grade.
74. Site plans shall include all overhead utility lines adjacent to the site.
75. Where access for a given development requires accommodation of Fire Department apparatus, overhead clearance shall not be less than 14 feet.
76. The Fire Department may require additional vehicular access where buildings exceed 28 feet in height.
77. Smoke Vents may be required where roof access is not possible; location and number of vents to be determined at Plan Review.
78. No proposed development utilizing cluster, group, or condominium design of one or two family dwellings shall be more than 150 feet from the edge of the roadway of an improved street, access road, or designated fire lane.
79. On small lot subdivisions, any lots used for access purposes shall be recorded on the final map as a "Fire Lane".
80. Private development shall conform to the standard street dimensions shown on Department of Public Works Standard Plan S-470-0.
81. Standard cut-corners will be used on all turns.
82. Where above ground floors are used for residential purposes, the access requirement shall be interpreted as being the horizontal travel distance from the street, driveway, alley, or designated fire lane to the main entrance of individual units.
83. The following recommendations of the Fire Department relative to fire safety shall be incorporated into the building plans, which includes the submittal of a plot plan for approval by the Fire Department either prior to the recordation of a final map or the approval of a building permit. The plot plan shall include the following minimum design features: fire lanes, where required, shall be a minimum of 20 feet in width; all structures must be within 300 feet of an approved fire hydrant, and entrances to any dwelling unit or guest room shall not be more than 150 feet in distance in horizontal travel from the edge of the roadway of an improved street or approved fire lane.

84. FPB #105

5101.1 Emergency responder radio coverage in new buildings. All new buildings shall have approved radio coverage for emergency responders within the building based upon the existing coverage levels of the public safety communication systems of the jurisdiction at the exterior of the building. This section shall not require improvement of the existing public safety communication systems.

85. That in order to provide assurance that the proposed common fire lane and fire protection facilities, for the project, not maintained by the City, are properly and adequately maintained, the sub-divider shall record with the County Recorder, prior to the recordation of the final map, a covenant and agreement (Planning Department General Form CP-6770) to assure the following:

- a. The establishment of a property owners association, which shall cause a yearly inspection to be, made by a registered civil engineer of all common fire lanes and fire protection facilities. The association will undertake any necessary maintenance and corrective measures. Each future property owner shall automatically become a member of the association or organization required above and is automatically subject to a proportionate share of the cost.
- b. The future owners of affected lots with common fire lanes and fire protection facilities shall be informed of their responsibility for the maintenance of the devices on their lots. The future owner and all successors will be presented with a copy of the maintenance program for their lot. Any amendment or modification that would defeat the obligation of said association as the Advisory Agency must approve required hereinabove in writing after consultation with the Fire Department.
- c. In the event that the property owners association fails to maintain the common property and easements as required by the CC and R's, the individual property owners shall be responsible for their proportional share of the maintenance.
- d. Prior to any building permits being issued, the applicant shall improve, to the satisfaction of the Fire Department, all common fire lanes and install all private fire hydrants to be required.
- e. That the Common Fire Lanes and Fire Protection facilities be shown on the Final Map.

86. The plot plans shall be approved by the Fire Department showing fire hydrants and access for each phase of the project prior to the recording of the final map for that phase. Each phase shall comply independently with code requirements.

87. Any roof elevation changes in excess of 3 feet may require the installation of ships ladders.

88. Provide Fire Department pathway front to rear with access to each roof deck via gate or pony wall less than 36 inches.

89. Where rescue window access is required, provide conditions and improvements necessary to meet accessibility standards as determined by the Los Angeles Fire Department.

90. Adequate off-site public and on-site private fire hydrants may be required. Their number and location to be determined after the Fire Department's review of the plot plan
91. Any required fire hydrants to be installed shall be fully operational and accepted by the Fire Department prior to any building construction.

DEPARTMENT OF WATER AND POWER

Questions regarding WSO clearance should be directed to the Los Angeles Department of Water and Power, Water Distribution Engineering, P.O. Box 51111, Room 1425, Los Angeles, California 90051-5700 or (213) 367-1241.

92. Satisfactory arrangement shall be made with the Los Angeles Department of Water and Power (LADWP) for compliance with LADWP's Water System Rules and requirements. Upon compliance with these conditions and requirements, LADWP's Water Services Organization will forward the necessary clearances to the Bureau of Engineering. (This condition shall be deemed cleared at the time the City Engineer clears Condition No. S-1(c).)

Note:

If improvements are proposed within existing dedicated streets, we [LADWP] must review your preliminary street improvement plans. If adjustments to water facilities are necessary, the developer may be required to pay for the cost of such adjustments. Please submit a copy of your street improvement plans after the City's District Engineer has signed them so that we can expedite determination of the need for adjustments.

BUREAU OF STREET LIGHTING

93. Prior to the recordation of the final map or issuance of the Certificate of Occupancy (C of O), street lighting improvement plans shall be submitted for review and the owner shall provide a good faith effort via a ballot process for the formation or annexation of the property within the boundary of the development into a Street Lighting Maintenance Assessment District.

BUREAU OF SANITATION

94. The office of LA Sanitation/CWCD – Clean Water North Conveyance Division has reviewed the sewer/storm drain lines serving the subject tracts/areas, and found no potential problems to its structures and/or potential maintenance issues.

This approval is for the Tract Map only and represents the office of LA Sanitation/CWCDs. The applicant may be required to obtain other necessary Clearances/Permits from LA Sanitation and appropriate District office of the Bureau of Engineering.

URBAN FORESTRY

95. Native Protected Trees
 - a. All tree and shrub preservation measures shall be considered to retain all protected native species whenever possible. Project should include feasible alternatives in project design to retain native trees and shrubs. A permit is required for the removal of any native protected tree and shrub. Removal of any on site native tree or shrub shall be replaced in kind at a 4: 1 ratio as approved by the Board of Public Works and Urban Forestry Division. The tree replacement plan shall include all retained native

trees and shrubs. All on-site tree and shrub replacements shall be planted in locations favorable to the long term survival of the species.

- b. The applicant shall submit a Protected Tree Report with an acceptable tree and shrub replacement plan prepared by a reputable Tree Expert, as required by Ordinance No. 186,873 for approval by the Advisory Agency and the Bureau of Street Services, Urban Forestry Division. The Protected Tree Report (PTR) shall contain the Tree Expert's recommendations for the preservation of as many protected trees as possible and shall provide their species, health, size, and condition. The PTR shall include a topographical map (construction drawing) identifying tree and shrub location, drip line, and correctly numbered and plotted.

Note: Removal of Native Protected trees and shrubs requires approval from the Board of Public Works. All projects must have environmental (CEQA) documents that appropriately address any removal and replacement of native protected trees and shrubs. Contact Urban Forestry Division at: (213) 847-3077 for tree removal permit information.

96. Street Trees

- a. Project shall preserve all healthy mature street trees whenever possible. All feasible alternatives in project design should be considered and implemented to retain healthy mature street trees. A permit is required for the removal of any street tree and shall be replaced 2:1 as approved by the Board of Public Works and Urban Forestry Division.
- b. Plant street trees at all feasible planting locations within dedicated streets as directed and required by the Bureau of Street Services, Urban Forestry Division. All tree plantings shall be installed to current tree planting standards when the City has previously been paid for tree plantings. The sub divider or contractor shall notify the Urban Forestry Division at: (213) 847-3077 upon completion of construction for tree planting direction and instructions.

Note: Removal of street trees requires approval from the Board of Public Works. All projects must have environmental (CEQA) documents that appropriately address any removal and replacement of street trees. Contact Urban Forestry Division at: (213) 847-3077 for tree removal permit information.

INFORMATION TECHNOLOGY AGENCY

97. To assure that cable television facilities will be installed in the same manner as other required improvements, please email cabletv.ita@lacity.org that provides an automated response with the instructions on how to obtain the Cable TV clearance. The automated response also provides the email address of 3 people in case the applicant/owner has any additional questions.

HOUSING ELEMENT STREAMLINING CHECKLIST ENVIRONMENTAL CONDITIONS

98. The Mitigation Monitoring Program (MMP) included in the Housing Element Streamlining Checklist (Case No. ENV-2023-6117-HES have been incorporated into this project and shall be enforced through all phases of the project. The applicant shall be responsible for implementing each Mitigation Measure (MM), Substitute Mitigation Measure, and Implementing Mitigation Measure identified in the MMP and shall be obligated to provide

certification to the appropriate monitoring and enforcement agencies that each MM has been implemented.

99. As outlined in the HE Streamlining Checklist that was prepared for the subject project, the project shall use construction equipment that meets the CARB Tier 4 Final or USEPA Tier 4 off-road emissions for all equipment rated 50 horsepower or greater. A copy of each unit's certified tier specification or model year specification and CARB or SCAQMD operating permit (if applicable) shall be available upon request at the time of mobilization of each applicable unit of equipment.

100. **Inadvertent Discovery of Archaeological Resources.** In the event that any subsurface cultural resources are encountered at the project site during construction or the course of any ground disturbance activities, all such activities shall halt immediately, pursuant to State Health and Safety Code Section 7050.5. The applicant shall notify the City and consult with a qualified archaeologist who shall evaluate the find in accordance with Federal, State, and local guidelines, including those set forth in the California Public Resources Code Section 21083.2 and shall determine the necessary findings as to the origin and disposition to assess the significance of the find. If any find is determined to be significant, appropriate avoidance measures recommended by the qualified archaeologist and approved by the Department of City Planning must be followed unless avoidance is determined to be unnecessary or infeasible by the qualified archaeologist. If avoidance is unnecessary or infeasible, other appropriate measures (e.g., data recovery, excavation) shall be instituted.

DEPARTMENT OF CITY PLANNING-SITE SPECIFIC CONDITIONS

101. Prior to the recordation of the final map, the subdivider shall prepare and execute a Covenant and Agreement (Planning Department General Form CP-6770) in a manner satisfactory to the Planning Department, binding the subdivider and all successors to the following:

- a. A Certificate of Occupancy (temporary or final) for the building(s) in Vesting Tentative Tract Map No. 84089-SL-HCA shall not be issued until after the final map has been recorded.
- b. Limit the tract to a maximum of twelve (12) small lots.
- c. Parking shall be provided in accordance with the LAMC.
- d. The Advisory Agency has approved a minimum 16-foot wide common access driveway (easement) with a minimum of 10 feet in width that is clear to the sky for the approved subdivision.
- e. A minimum of one common access walkway (easement) shall provide pedestrian access from a public street to the subdivision. The common access walkway(s) must be a minimum of 3 feet in width and remain unobstructed and open to the sky.
- f. Prior to issuance of a certificate of occupancy, a minimum 6-foot-high fence or wall made of slumpstone, decorative masonry, or other comparable-quality material shall be constructed adjacent to neighboring residences, if no such wall already exists, except in required front yard.
- g. No vehicular gates shall be permitted within the development.

- h. The applicant shall seek and obtain any necessary approvals for any proposed ADUs and JADUs. No construction or siting of any ADUs or JADUs have been authorized herein.
 - i. That a solar access report shall be submitted to the satisfaction of the Advisory Agency prior to obtaining a grading permit.
 - j. That the subdivider considers the use of natural gas and/or solar energy and consults with the Department of Water and Power and Southern California Gas Company regarding feasible energy conservation measures.
 - k. A utility easement shall be provided per Department of Water and Power or similar agency requirements.
 - l. Recycling bins shall be provided at appropriate locations to promote recycling of paper, metal, glass, and other recyclable material.
 - m. The applicant shall install shielded lighting to reduce any potential illumination affecting adjacent properties.
 - n. A Maintenance Agreement shall be formed, composed of all small-lot property owners, to maintain all common areas such as trees, landscaping, trash, parking, community driveway, walkways, monthly service for private fire hydrant (if required), etc. Each small-lot owner and future small-lot property owners shall automatically become members of the agreement and shall be subject to a proportionate share of the maintenance. The Maintenance Agreement shall be recorded as a Covenant and Agreement to run with the land. The subdivider shall submit a copy of this Agreement, once recorded to the Planning Department for placement in the tract file.
 - o. Copies of all recorded Covenant and Agreement(s) for all reciprocal private easements shall be submitted to the Planning Department for placement in the tract file.
102. The approval of Vesting Tentative Tract Map No. 84089-SL-HCA shall be contingent upon the approval of Case No. CPC-2023-6115-DB-HCA.
103. Prior to the issuance of building permits, the Applicant shall explore further design modifications with the Urban Design Studio to the satisfaction of the City Planning Department, Expedited Processing Section.
104. Prior to the clearance of any tract map conditions, the applicant shall show proof that all fees have been paid to the Department of City Planning, Expedited Processing Section.
105. If applicable, within 10 days after the time to appeal has expired, the applicant shall execute and record a Covenant and Agreement (Planning Department General Form CP-6770) in a form satisfactory to the Advisory Agency binding the applicant and any successor in interest to provide tenant relocation assistance and establish a relocation program in a manner consistent with Section 47.07 of the LAMC relating to demolition. A copy shall be provided to each eligible tenant within five days of recordation of the covenant and agreement.
106. **Indemnification and Reimbursement of Litigation Costs.** Applicant shall do all of the following:
- a. Defend and hold harmless the City from any and all actions against the City relating to or arising out of, in whole or in part, the City's processing and approval of this

entitlement, including but not limited to, an action to attack, challenge, set aside, void, or otherwise modify or annul the approval of the entitlement, the environmental review of the entitlement, or the approval of subsequent permit decisions, or to claim personal property damage, including from inverse condemnation or any other constitutional claim.

- b. Reimburse the City for any and all costs incurred in defense of an action related to or arising out of, in whole or in part, the City's processing and approval of the entitlement, including but not limited to payment of all court costs and attorney's fees, costs of any judgment or awards against the City (including an award of attorney's fees), damages, and/or settlement costs.
- c. Submit an initial deposit for the City's litigation costs to the City within 10 days' notice of the City tendering defense to the applicant and requesting a deposit. The initial deposit shall be in an amount set by the City Attorney's Office, in its sole discretion, based on the nature and scope of action, but in no event shall the initial deposit be less than \$50,000. The City's failure to notice or collect the deposit does not relieve the applicant from responsibility to reimburse the City pursuant to the requirement in paragraph (b).
- d. Submit supplemental deposits upon notice by the City. Supplemental deposits may be required in an increased amount from the initial deposit if found necessary by the City to protect the City's interests. The City's failure to notice or collect the deposit does not relieve the Applicant from responsibility to reimburse the City pursuant to the requirement in paragraph (b).
- e. If the City determines it necessary to protect the City's interests, execute the indemnity and reimbursement agreement with the City under terms consistent with the requirements of this condition.
- f. The City shall notify the applicant within a reasonable period of time of its receipt of any action and the City shall cooperate in the defense. If the City fails to notify the applicant of any claim, action, or proceeding in a reasonable time, or if the City fails to reasonably cooperate in the defense, the applicant shall not thereafter be responsible to defend, indemnify, or hold harmless the City.

The City shall have the sole right to choose its counsel, including the City Attorney's office or outside counsel. At its sole discretion, the City may participate at its own expense in the defense of any action, but such participation shall not relieve the applicant of any obligation imposed by this condition. In the event that applicant fails to comply with this condition, in whole or in part, the City may withdraw its defense of the action, void its approval of the entitlement, or take any other action. The City retains the right to make all decisions with respect to its representations in any legal proceeding, including its inherent right to abandon or settle litigation.

For purposes of this condition, the following definitions apply:

"City" shall be defined to include the City, its agents, officers, boards, commissions, committees, employees, and volunteers.

"Action" shall be defined to include suits, proceedings (including those held under alternative dispute resolution procedures), claims, or lawsuits. Actions include actions, as defined herein, alleging failure to comply with any federal, state or local

law.

Nothing in the definitions included in this paragraph are intended to limit the rights of the City or the obligations of the applicant otherwise created by this condition.

DEPARTMENT OF CITY PLANNING - STANDARD SMALL LOT HOME CONDITIONS

SL-1. That approval of this vesting tentative tract map constitutes approval of model home uses, including a sales office and off-street parking. If models are constructed under this tract map approval, the following conditions shall apply:

1. Prior to recordation of the final map, the subdivider shall submit a plot plan for approval by the Division of Land Section of the Department of City Planning showing the location of the model dwellings, sales office and off-street parking. The sales office must be within one of the model buildings.
2. All other conditions applying to Model Dwellings under Section 12.22 A.10 and 11 and Section 17.05 O of the LAMC shall be fully complied with satisfactory to the Department of Building and Safety.

SL-2. That a landscape plan, prepared by a licensed landscape architect, be submitted to and approved by the Advisory Agency following the instructions of Form CP-6730 prior to obtaining any grading or building permits before the recordation of the final map. The landscape plan shall identify tree replacement on a 1:1 basis by a minimum of 24-inch box trees for the unavoidable loss of desirable trees on the site.

In the event the subdivider decides not to request a permit before the recordation of the final map, a covenant and agreement satisfactory to the Advisory Agency guaranteeing the submission of such plan before obtaining any permit shall be recorded.

BUREAU OF ENGINEERING - STANDARD CONDITIONS

- S-1. (a) That the sewerage facilities charge be deposited prior to recordation of the final map over all of the tract in conformance with Section 64.11.2 of the LAMC.
- (b) That survey boundary monuments be established in the field in a manner satisfactory to the City Engineer and located within the California Coordinate System prior to recordation of the final map. Any alternative measure approved by the City Engineer would require prior submission of complete field notes in support of the boundary survey.
- (c) That satisfactory arrangements be made with both the Water System and the Power System of the Department of Water and Power with respect to water mains, fire hydrants, service connections and public utility easements.
- (d) That any necessary sewer, street, drainage and street lighting easements be dedicated. In the event it is necessary to obtain off-site easements by separate instruments, records of the Bureau of Right-of-Way and Land shall verify that such easements have been obtained. The above requirements do not apply to easements of off-site sewers to be provided by the City.
- (e) That drainage matters be taken care of satisfactory to the City Engineer.

- (f) That satisfactory street, sewer and drainage plans and profiles as required, together with a lot grading plan of the tract and any necessary topography of adjoining areas be submitted to the City Engineer.
 - (g) That any required slope easements be dedicated by the final map.
 - (h) That each lot in the tract complies with the width and area requirements of the Zoning Ordinance.
 - (i) That one-foot future streets and/or alleys be shown along the outside of incomplete public dedications and across the termini of all dedications abutting unsubdivided property. The one-foot dedications on the map shall include a restriction against their use of access purposes until such time as they are accepted for public use.
 - (j) That any one-foot future street and/or alley adjoining the tract be dedicated for public use by the tract, or that a suitable resolution of acceptance be transmitted to the City Council with the final map.
 - (k) That no public street grade exceeds 15 percent.
 - (l) That any necessary additional street dedications be provided to comply with the Americans with Disabilities Act (ADA) of 2010.
- S-2. That the following provisions be accomplished in conformity with the improvements constructed herein:
- (a) Survey monuments shall be placed and permanently referenced to the satisfaction of the City Engineer. A set of approved field notes shall be furnished, or such work shall be suitably guaranteed, except where the setting of boundary monuments requires that other procedures be followed.
 - (b) Make satisfactory arrangements with the Department of Transportation with respect to street name, warning, regulatory and guide signs.
 - (c) All grading done on private property outside the tract boundaries in connection with public improvements shall be performed within dedicated slope easements or by grants of satisfactory rights of entry by the affected property owners.
 - (d) All improvements within public streets, private street, alleys and easements shall be constructed under permit in conformity with plans and specifications approved by the Bureau of Engineering.
 - (e) Any required bonded sewer fees shall be paid prior to recordation of the final map.
- S-3. That the following improvements be either constructed prior to recordation of the final map or that the construction be suitably guaranteed:
- (a) Construct on-site sewers to serve the tract as determined by the City Engineer.
 - (b) Construct any necessary drainage facilities.

- (c) No street lighting improvements if no street widening per BOE improved conditions. Otherwise, relocate and upgrade street light: one (1) on Preuss Road.
- (d)
 - 1) Native Protected Trees
 - i. All tree and shrub preservation measures shall be considered to retain all protected native species whenever possible. Project should include feasible alternatives in project design to retain native trees and shrubs. A permit is required for the removal of any native protected tree and shrub. Removal of any on site native tree or shrub shall be replaced in kind at a 4: 1 ratio as approved by the Board of Public Works and Urban Forestry Division. The tree replacement plan shall include all retained native trees and shrubs. All on-site tree and shrub replacements shall be planted in locations favorable to the long term survival of the species.
 - ii. The applicant shall submit a Protected Tree Report with an acceptable tree and shrub replacement plan prepared by a reputable Tree Expert, as required by Ordinance No. 186,873 for approval by the Advisory Agency and the Bureau of Street Services, Urban Forestry Division. The Protected Tree Report (PTR) shall contain the Tree Expert's recommendations for the preservation of as many protected trees as possible and shall provide their species, health, size, and condition. The PTR shall include a topographical map (construction drawing) identifying tree and shrub location, drip line, and correctly numbered and plotted.
 - 2) Street Trees
 - i. Project shall preserve all healthy mature street trees whenever possible. All feasible alternatives in project design should be considered and implemented to retain healthy mature street trees. A permit is required for the removal of any street tree and shall be replaced 2:1 as approved by the Board of Public Works and Urban Forestry Division.
 - ii. Plant street trees at all feasible planting locations within dedicated streets as directed and required by the Bureau of Street Services, Urban Forestry Division. All tree plantings shall be installed to current tree planting standards when the City has previously been paid for tree plantings. The sub divider or contractor shall notify the Urban Forestry Division at: (213) 847-3077 upon completion of construction for tree planting direction and instructions.
- (e) Repair or replace any off-grade or broken curb, gutter and sidewalk satisfactory to the City Engineer.
- (f) Construct access ramps for the handicapped as required by the City Engineer.
- (g) Close any unused driveways satisfactory to the City Engineer.
- (h) Construct any necessary additional street improvements to comply with the

Americans with Disabilities Act (ADA) of 2010.

- (i) That the following improvements be either constructed prior to recordation of the final map or that the construction be suitably guaranteed:
 - a) Improve Preuss Road being dedicated and adjoining the subdivision by the construction of the following:
 - a. A concrete curb, a concrete gutter, and a 12-foot wide concrete sidewalk with tree wells or a 5-foot wide concrete sidewalk and landscaping of the parkway.
 - b. Suitable surfacing to join the existing pavement and to complete an 18-foot half roadway.
 - c. Any necessary removal and reconstruction of existing improvements.
 - d. The necessary transitions to join the existing improvement.
 - b) Improve the alley adjoining the subdivision by the construction of a new 2-foot wide longitudinal concrete gutter and suitable surfacing to complete a 10-foot wide half alley, including any necessary removal and reconstruction of the existing improvements.
 - c) Construct the necessary on-site mainline and house connection sewers satisfactory to the City Engineer.

ENVIRONMENTAL MITIGATION MEASURES

Geology and Soils:

MM GEO-4.5-1(a)

Because the project is discretionary and involves excavation or grading activities at depths greater than previous disturbance on the respective site(s), the project has conducted a resource assessment and records search for the presence of paleontological resources to determine if the project site is underlain by paleontological resources; it shall monitor all excavation and grading activities in areas underlain by soils or geologic units potentially containing paleontological resources; and identify, record, and evaluate all paleontological resources uncovered during project construction and submit a paleontological assessment report to the City for review and approval. In addition, during project construction, the following shall be conducted: cease all construction activities in the event of the discovery of paleontological resources; conduct fossil recovery as necessary by a qualified paleontologist; avoid handling of paleontological resources by parties other than the qualified paleontologist responsible for conducting fossil recovery; and resume construction activities only upon clearance by the qualified paleontologist. These procedures, as detailed below, shall be implemented to avoid impacts to paleontological resources or reduce potential impacts to a less-than-significant level:

1. All mitigation programs shall be performed by a qualified professional (project) paleontologist, defined as an individual with a master's or doctorate in paleontology or geology, who has proven experience and is knowledgeable in professional paleontological procedures and techniques. Fieldwork may be conducted by a qualified paleontological

monitor, defined as an individual who has experience in the collection and salvage of fossil materials. The paleontological monitor shall always work under the direction of a qualified paleontologist.

2. Starting at the surface, monitoring shall be conducted full-time in areas of grading or excavation in undisturbed Pleistocene-aged old paralic/alluvial deposits.
3. Paleontological monitors will be equipped to salvage fossils as they are unearthed to avoid construction delays. The monitor must be empowered to temporarily halt or divert equipment to allow removal of abundant or large specimens in a timely manner. Monitoring may be reduced if the potentially fossiliferous units are not present in the subsurface, or, if present, are determined upon exposure and examination by qualified paleontological personnel to have low potential to contain fossil resources. The monitor shall notify the project paleontologist, who will then notify any concerned parties of the discovery.
4. Paleontological salvage during trenching and boring activities is typically from the generated spoils and will not delay trenching or drilling activities. Fossils will be collected and placed in cardboard flats or plastic buckets and identified by field number, collector, and date collected. Before the site is vacated and the fossils are moved to a safe place, notes are taken on the map location and stratigraphy of the site. On mass grading projects, discovered fossil sites are protected by flagging to prevent them from being overrun by earthmovers (scrapers) before salvage begins. Fossils will be collected in a similar manner, with notes and photographs being taken before removing the fossils. Precise location of the site is determined through use of handheld Global Positioning System units. If a large terrestrial vertebrate that is too large to be easily removed by a single monitor, such as a large bone or a mammoth tusk, is found, a fossil recovery crew shall excavate around the find(s), encase the find(s) within a plaster and burlap jacket, and remove the find(s) after the plaster is set. For large fossils, use of the contractor's construction equipment may be solicited to help move the jacket to a safe location.
5. In alluvial deposits, small invertebrate fossils typically represent multiple specimens of a limited number of species, and a scientifically suitable sample can be obtained from one to several five-gallon buckets of fossiliferous sediment. If it is possible to dry screen the sediment in the field, a concentrated sample may consist of one or two buckets of material to check for the presence of invertebrates
6. In accordance with the "Microfossil Salvage" section of the Society of Vertebrate Paleontology guidelines (2010:7), bulk sampling and screening of fine-grained sedimentary (alluvial) deposits (including carbonate-rich paleosols) must be performed if the deposits are identified to possess indications of producing fossil "microvertebrates" to test the feasibility of the deposit to yield fossil bones and teeth. If indicators of potential microvertebrate fossils are found, screening of a test sample (approximately 600 pounds) is recommended, according to the Society of Vertebrate Paleontology guidelines. If feasible, wet screening shall be conducted on the project site. If screening yields significant fossils, then removing and processing a "standard sample" of 6,000 pounds shall be performed.

7. In the laboratory, individual fossils will be cleaned of extraneous matrix, any breaks will be repaired, and the specimen, if needed, will be stabilized by soaking in an archivally approved acrylic hardener (e.g., a solution of acetone and Paraloid B-72).
8. Recovered specimens will be prepared to a point of identification and permanent preservation (not display), including screen-washing sediments to recover small invertebrates and vertebrates. Preparation of individual vertebrate fossils is often more time-consuming than for accumulations of invertebrate fossils.
9. Identification and curation of specimens into a professional, accredited public museum repository with a commitment to archival conservation and permanent retrievable storage (e.g., the Los Angeles County Museum of Natural History) shall be conducted. The paleontological program should include a written repository agreement prior to initiating mitigation activities. Prior to curation, the lead agency (the City of Los Angeles) will be consulted on the repository/museum to receive the fossil material.
10. A final report of findings and significance will be prepared, including lists of all fossils recovered and necessary maps and graphics to accurately record their original location(s). The report, when submitted to and accepted by the appropriate lead agency, will signify satisfactory completion of the project program to mitigate impacts to any potential nonrenewable paleontological resources (i.e., fossils) that might have been lost or otherwise adversely affected without such a program in place.

MM GEO-4.5-1(b)

The cultural resources assessment under MM 4.5-1(a) determined that this MM is required, therefore, prior to the start of construction, a paleontological monitor shall conduct training for construction personnel regarding the appearance of fossils and the procedures for notifying paleontological staff should fossils be discovered by construction staff, and notice that the identified qualified paleontologist is the only one authorized to handle paleontological find(s), including but not limited to collection and removal. Approved plans shall include statement of WEAP requirement.

MM GEO-4.5-1(c)

As determined by the cultural resources assessment under MM 4.5-1(a), a paleontologist or designated paleontological monitor shall monitor ground disturbance activities, including the initial five feet below the ground surface, as areas with high paleontological sensitivity may contain resources at shallow depths and within the first five feet. If the paleontological monitor determines that full-time monitoring is no longer warranted, he or she may recommend that monitoring be reduced to periodic spot-checking or cease entirely. Monitoring shall be reinstated if any new or unforeseen deeper ground disturbances are required. After ground disturbing activities are completed, the paleontologist or designated monitor shall complete and submit a report to the City verifying compliance with the monitoring plan. Monitoring plan shall show on the plans.

MM GEO-4.5-1(d)

Discovery. If paleontological resources are uncovered during construction activities (in either a previously disturbed or undisturbed area), all ground-disturbing activities in the area of the find

shall cease until a qualified paleontologist has evaluated the find, and identified and prepared an appropriate mitigation plan, in accordance with federal, state, and local guidelines, Construction activities in the area of the discovery shall commence again only after the identified resource(s) are properly processed by a qualified paleontologist, and if construction activities are cleared by the qualified paleontologist to continue. If cleared by the qualified paleontologist, construction activity may continue unimpeded on other portions of the project site that would not affect evaluation or recovery of the identified resource(s).

Fossil Salvage and Treatment. The qualified paleontologist or designated paleontological monitor shall recover intact fossils consistent with the mitigation plan and notify the City of any fossil salvage and recovery efforts. Typically, fossils can be safely salvaged quickly by a single paleontologist and not disrupt construction activity. In some cases, larger fossils (such as complete skeletons or large mammal fossils) require more extensive excavation and longer salvage periods. In this case the paleontologist shall have the authority to temporarily direct, divert or halt construction activity to ensure that the fossil(s) can be removed in a safe and timely manner. Any fossils shall be handled and deposited consistent with a mitigation plan prepared by the paleontological monitor. The qualified paleontologist shall prepare a report according to current professional standards including those of the SVP that describes the resource, how it was assessed, and disposition. The report shall be submitted to the City. The requirements in this mitigation measure shall be shown on plans.

Noise:

MM NOISE-4.10-1(a)

Power construction equipment (including combustion engines), fixed or mobile, shall be equipped with noise shielding and silencing devices consistent with manufacturer's standards or the Best Available Control Technology. Equipment shall be properly maintained, and the Project Applicant or Owner shall require any construction contractor to keep documentation on-site during any earthwork or construction activities demonstrating that the equipment has been maintained in accordance with manufacturer's specifications. Measure shall be shown on plans.

MM NOISE-4.10-1(b)

Driven (impact), sonic, or vibratory pile drivers shall not be used, except in locations where the underlying geology renders alternative methods infeasible, as determined by a soils or geotechnical engineer and documented in a soils report. Requirement shall show on plans.

MM NOISE-4.10-1(c)

All outdoor mechanical equipment shall be enclosed or screened from off-site noise-sensitive uses. The equipment enclosure or screen shall be impermeable (i.e., solid material with minimum weight of 2 pounds per square feet) and break the line-of-sight from the equipment and off-site noise-sensitive uses.

MM NOISE-4.10-1(d)

Construction staging areas shall be located as far from noise-sensitive uses as reasonably possible and feasible in consideration of site boundaries, topography, intervening roads and uses, and operational constraints. Requirement shall show on plans.

MM NOISE-4.10-1(e)

Sound barriers, such as temporary walls or sound blankets, shall be erected between construction activities and noise-sensitive uses when construction activities are located within a line-of-sight to and within 500 feet of noise-sensitive uses. Requirement shall show on plans.

MM NOISE-4.10-3(b)

- Impact pile drivers shall be avoided to eliminate excessive vibration levels. Drilled piles or similar methods are alternatives that shall be utilized where geological conditions permit their use.
- Construction activities shall involve rubber-tired equipment rather than metal-tracked equipment.

The construction contractor shall manage construction phasing (scheduling demolition, earthmoving, and ground-impacting operations so as not to occur in the same time period), use low-impact construction technologies, and shall avoid the use of vibrating equipment when allowed by best engineering practices. Requirement to be on plans.

Tribal Cultural Resources:

MM TRIB-4.15-1(b)

In the event that Tribal Cultural Resources are discovered during Project activities, whether or not a tribal monitor is present, and there is no CRMP or the CRMP does not cover treatment of inadvertent discovery, all work within a 50-foot buffer of the find shall cease and a Qualified Archaeologist meeting the Secretary of the Interior's Professional Qualification Standards for Archaeology shall assess the find. Tribes that are culturally and historically affiliated with the Project area and have requested consultation shall be notified, should any potential tribal cultural resource be discovered during project implementation. Construction personnel shall not collect or move any tribal resources. Construction activity may continue unimpeded on other portions of the project site. Unless agreed otherwise during the tribal consultation process or in a CRMP, if tribal cultural resources are discovered during construction, the applicant and/or owner shall retain a Qualified Tribal Monitor (as approved by the Tribe) if requested by the Tribe. Any and all archaeological/cultural documents created as a part of the Project (isolate records, site records, survey reports, testing reports, and monitoring reports) should be provided to consulting Tribes. Any tribal cultural resources discovered shall be treated with appropriate dignity and protected and preserved as appropriate with the agreement of the Tribal Representative and in accordance with federal, state, and local guidelines.

If not otherwise provided in the CRMP, the Lead Agency and/or applicant shall, in good faith, provide all consulting Tribes the opportunity to consult on the disposition and treatment of resources. The location of the find of tribal cultural resources and the type and nature of the find will not be published, except to provide information to the Qualified Archaeologist, tribal representatives, and public agencies with jurisdiction or responsibilities related to the resources. An agreement will be reached with the Tribal Representative to mitigate or avoid any significant impacts to identified tribal cultural resources. Absent an agreement with the Tribal Representative, as provided in Public Resources Code Section 21083.2, the find should be preserved in place or left in an undisturbed state unless the Project would damage the resource. When preserving in place or leaving in an undisturbed state is not possible, excavation should not occur until testing or studies prepared by a Qualified Archaeologist have adequately documented the recovery of scientifically consequential information from and about the resource. Construction activity may

continue unimpeded on other portions of the project site if cleared by the Qualified Tribal Monitor or Qualified Archaeologist. Ground Disturbance Activities in the area where resources were found may commence once the identified resources are properly assessed and processed by a Tribal Representative or, if no Tribal Representative is identified, a Qualified Archaeologist. The measure shall be shown on plans.

NOTES:

The Advisory Agency approval is the maximum number of units permitted under the tract action. However, the existing or proposed zoning may not permit this number of units.

Approval from Board of Public Works may be necessary before removal of any street trees in conjunction with the improvements in this tract map through Bureau of Street Services Urban Forestry Division.

Satisfactory arrangements shall be made with the Los Angeles Department of Water and Power, Power System, to pay for removal, relocation, replacement or adjustment of power facilities due to this development. The subdivider must make arrangements for the underground installation of all new utility lines in conformance with LAMC Section 17.05-N.

The final map must record within 36 months of this approval, unless a time extension is granted before the end of such period.

The Advisory Agency hereby finds that this tract conforms to the California Water Code, as required by the Subdivision Map Act.

The subdivider should consult the Department of Water and Power to obtain energy saving design features which can be incorporated into the final building plans for the subject development. As part of the Total Energy Management Program of the Department of Water and Power, this no-cost consultation service will be provided to the subdivider upon his request.